



Telepresence Interoperability Protocol (“TIP”) Implementation Profile Evaluation Sublicense

Published July 2010

THIS IS A TIME-LIMITED EVALUATION SUBLICENSE THAT PROVIDES YOU WITH THE RIGHT TO EVALUATE A TIP IMPLEMENTATION PROFILE SPECIFICATION FOR NINETY (90) DAYS FOLLOWING YOUR INITIAL DOWNLOAD OR ACCESS.

This is a legal agreement (“Evaluation Sublicense”) between the International Multimedia Telecommunications Consortium (“IMTC”) and an individual or entity (“You”) interested in downloading the attached Telepresence Interoperability Protocol Implementation Profile Specification (a “TIP Profile Specification”) solely for purposes of evaluation. Cisco Systems, inc. (“Cisco”) is an intended third-party beneficiary of this Evaluation Sublicense.

The attached TIP Implementation Profile Specification provides information regarding Cisco’s implementation of the Telepresence Interoperability Protocol, which is a protocol for interoperability between videoconferencing products, including streaming of audio, video, and data to and from videoconferencing products. IMTC offers this sublicense to encourage interoperability between competitive videoconferencing products that exist as of the date of this sublicense or that may come to exist in the future. TIP means the specification found at [IMTC web site].

Only a TIP Profile Specification published by Cisco and licensed to IMTC will be considered a TIP Profile Specification for purposes of this Evaluation Sublicense. Any specification not published by Cisco and licensed to IMTC, or one that incorporates a TIP Profile Specification in part, in whole, or by reference shall not be considered the TIP Profile Specification for purposes of this Evaluation Sublicense.

BY ACCESSING OR DOWNLOADING THE ATTACHED TIP PROFILE SPECIFICATION FOR EVALUATION PURPOSES, YOU AGREE TO BE BOUND BY THE TERMS OF THIS EVALUATION SUBLICENSE.

If You want a sublicense from IMTC to evaluate the attached TIP Profile Specification, You must agree to these terms. This is an offer to be accepted only on the terms set forth in this Evaluation Sublicense. You accept these terms by accessing, downloading, using, or reviewing the evaluation version of the attached TIP Profile Specification. Once accepted, IMTC grants You the sublicense below, provided that You fully comply with these terms. If You do not agree to any of these terms, then You are not licensed or sublicensed under this Evaluation Sublicense. If You attempt to alter or modify any of these terms, then the offer is no longer valid and is revoked.

Time-Limited Sublicense

The sublicense granted by this Evaluation Sublicense shall extend only for a period of ninety (90) days from the date on which you first download or access a TIP Profile Specification for the purpose of evaluation (“Limited Term”).

**EVALUATION COPY ONLY – NOT FOR IMPLEMENTATION.
USE SUBJECT TO EVALUATION SUBLICENSE AGREEMENT**



Immediately upon expiration of the Limited Term, this Evaluation Sublicense shall terminate automatically, without further notice to You. Upon expiration of this sublicense, You agree to discontinue any and all use of the TIP Profile Specification sublicensed to you under this Evaluation Sublicense and destroy any copies of the evaluation version of that TIP Profile Specification you have downloaded or otherwise created, and all extracts or summaries of the information embodied in that TIP Profile Specification.

Permitted Uses

SUBJECT TO THE TERMS AND CONDITIONS OF THE EVALUATION SUBLICENSE AND ONLY DURING THE LIMITED TERM, IMTC GRANTS YOU A LIMITED, NONEXCLUSIVE, PERSONAL, NONTRANSFERABLE SUBLICENSE TO DOWNLOAD AND USE THE ATTACHED TIP PROFILE SPECIFICATION SOLELY FOR PURPOSES OF YOUR EVALUATION, AND NOT FOR ANY OTHER PURPOSE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLEMENTATION OF THE TIP PROFILE SPECIFICATION OR THE DEVELOPMENT, MANUFACTURE, IMPORTATION, OR SALE OF ANY PRODUCTS. THIS EVALUATION SUBLICENSE DOES NOT GRANT A LICENSE OR SUBLICENSE TO ANY PATENT ESSENTIAL TO IMPLEMENT THE ATTACHED TIP PROFILE SPECIFICATION, WHETHER OWNED BY CISCO, IMTC, OR ANY THIRD PERSON. You may make only that number of copies of the attached TIP Specification as are necessary for Your evaluation. You may not otherwise copy the attached TIP Profile Specification. You may not distribute, modify, or create derivative works of the attached TIP Specification. No part of the attached TIP Profile Specification may be printed out, reproduced, distributed, resold, or transmitted for any other purpose, including, without limitation, commercial purposes, such as selling copies of the attached TIP Profile Specification or providing paid-for support services.

If you want to use the attached TIP Profile Specification beyond the Limited Term or want to use the attached TIP Profile Specification to implement or for any purpose other than for Your evaluation purpose, please go to [IMTC web site] to obtain a TIP Profile Implementation Profile Sublicense. You acknowledge that any use of the evaluation version of the attached TIP Profile Specification for any purpose prohibited under this Evaluation Sublicense, but permitted under the Implementation Sublicense subjects You to all terms of the Implementation Sublicense in the form in which it existed as of the date of your download, including, without limitation, the obligation to license patents essential to implement the attached TIP Profile to Cisco and any implementer of the attached TIP Profile.

Reservation of Rights

Cisco has licensed the attached TIP Profile Specification to IMTC and authorized IMTC to grant this sublicense. Except for its license and authorization to sublicense granted to IMTC, Cisco reserves all rights, title, and interest in and to the attached TIP Profile Specification. Cisco reserves the right to modify the TIP Profile Specification without notice to you. No right or license to any IMTC or Cisco intellectual property is granted under this Evaluation Sublicense for any use except the evaluation of the TIP Specification. All rights not expressly granted herein are reserved.

No Warranty

THE TIP PROFILE SPECIFICATION AND THE SUBLICENSE GRANTED UNDER THIS EVALUATION SUBLICENSE ARE PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS,

**EVALUATION COPY ONLY – NOT FOR IMPLEMENTATION.
USE SUBJECT TO EVALUATION SUBLICENSE AGREEMENT**



IMPLIED, OR STATUTORY, INCLUDING BUT NOT LIMITED TO WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE OR NON-INFRINGEMENT. NONE OF IMTC, ANY IMTC AFFILIATE, CISCO, OR ANY CISCO AFFILIATE SHALL HAVE ANY DUTY TO INDEMNIFY, HOLD HARMLESS OR DEFEND YOU OR ANY THIRD PARTY FROM AND AGAINST ANY LOSS, DAMAGE, LAWSUITS, PROCEEDINGS, CLAIMS OR SIMILAR ACTIONS THAT ARISE OR RESULT FROM YOUR EVALUATION OF THE TIP PROFILE SPECIFICATION, IN WHOLE OR IN PART.

Limitation Of Liability

NONE OF IMTC, ANY IMTC AFFILIATE, CISCO, OR ANY CISCO AFFILIATE SHALL BE LIABLE UNDER OR IN CONNECTION WITH THIS EVALUATION SUBLICENSURE (WHETHER FOR BREACH OF WARRANTY, IN CONTRACT, TORT, NEGLIGENCE, STRICT LIABILITY OR OTHERWISE):

- (A) FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, PUNITIVE OR INCIDENTAL DAMAGES; OR
- (B) FOR ANY DIRECT LOSSES, INCLUDING WITHOUT LIMITATION COSTS OF PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES, LOSS OF PROFITS, LOSS OF REVENUE, LOSS OF USE, LOSS OF OPPORTUNITY, INTERRUPTION OF BUSINESS; OR
- (C) FOR ANY LOSSES, DAMAGES, COSTS, CLAIMS OR OTHER LIABILITIES ARISING FROM OR RELATED TO THIS EVALUATION SUBLICENSURE WHATSOEVER,

IN EACH CASE HOWEVER CAUSED OR ARISING, PROVIDED THAT NOTHING IN THIS EVALUATION SUBLICENSURE SHALL EXCLUDE OR LIMIT THE LIABILITY OF IMTC, OR ANY IMTC AFFILIATE, OR CISCO, OR ANY CISCO AFFILIATE: (1) FOR DEATH OR PERSONAL INJURY RESULTING FROM ITS NEGLIGENCE; OR (2) FOR FRAUD; OR (3) TO THE EXTENT SUCH LIABILITY CANNOT BE EXCLUDED OR LIMITED BY APPLICABLE LAW. YOU ACKNOWLEDGE THAT (A) IMTC WOULD NOT HAVE ENTERED INTO THIS EVALUATION SUBLICENSURE ON THE TERMS HEREOF WITHOUT THE LIMITATIONS OF LIABILITY SET FORTH HEREIN; AND (B) THAT CISCO WOULD NOT HAVE LICENSED THE ATTACHED TIP PROFILE SPECIFICATION TO IMTC FOR IMTC'S SUBLICENSURE UNDER THIS EVALUATION SUBLICENSURE WITHOUT THE LIMITATIONS OF LIABILITY SET FORTH HEREIN.

Governing Law

This Evaluation Sublicensure shall be construed in accordance with, and all disputes hereunder shall be governed by, the laws of England and Wales. You consent to the personal and exclusive jurisdiction of the courts of England and Wales over You and waive any objection to venue in the courts of England and Wales.

General

This Evaluation Sublicensure is the only agreement between You and IMTC relating to is subject matter, and supersedes any prior agreement, understanding, or communication. This Evaluation Sublicensure and your rights under this Evaluation Sublicensure are personal to You and may not be assigned or transferred. Any assignment or transfer is null and void.

**EVALUATION COPY ONLY – NOT FOR IMPLEMENTATION.
USE SUBJECT TO EVALUATION SUBLICENSURE AGREEMENT**



Cisco TIP

Single Screen Endpoint 1.6b

Implementation Profile

(for use with TIP v6)

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

Modification History

Revision	Date	Originator	Comments
1.0	04/05/2010	Cisco Systems, Inc.	Initial document
1.1	04/22/2010	Cisco Systems, Inc.	Changed MUST to SHOULD for the Conference ID in 5.1.13 and modifications made software releases in 11.1
1.2	07/01/2010	Cisco Systems, Inc	Several corrections and clarifications outlined in section 11.3 through 11.9

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

1 Contents

1. INTRODUCTION	3
2 SINGLE SCREEN ENDPOINT GENERAL CAPABILITIES	4
3 SIP SIGNALING	4
3.1 SDP AUDIO SIGNALING	5
3.2 SDP VIDEO SIGNALING	6
4 SAMPLE SIP CALL FLOWS	9
4.1 ENDPOINT CALLING ANOTHER ENDPOINT	9
4.2 TIP ENDPOINT CALLING A TIP MULTI-POINT SERVER	10
4.3 TIP ENDPOINT CALLING A TIP MULTI-POINT SERVER AS THE FIRST PARTICIPANT	11
4.4 RESUMING A TIP CALL AFTER HOLD	11
4.5 REDUCING THE BIT RATE IN A CALL	11
5 INITIAL TIP SIGNALING	12
5.1 MUXCTRL PACKET	12
5.2 MEDIAOPTS PACKET	13
5.3 TIP NEGOTIATION AND GENERAL MID-SESSION SIGNALING RULES	14
6 PRESENTATION SIGNALING	15
6.1 TRANSMITTING AND RECEIVING PERMISSION-TO-PRESENT REQUESTS IN A MULTI-POINT SESSION	16
6.2 TRANSMITTING AND RECEIVING PERMISSION-TO-PRESENT REQUESTS IN A POINT-TO-POINT SESSION	16
6.3 TRANSMITTING AND RECEIVING PERMISSION-TO-PRESENT RELEASE REQUESTS	17
6.4 RECEIVING A REQUEST-TO-PRESENT GRANT IN A MULTI-POINT SESSION	18
7 PRESENTATION FRAME RATE NEGOTIATION	18
7.1 INITIAL FRAME RATE NEGOTIATION	18
7.2 SIGNALING A NEW FRAME RATE	18
8 AUDIO MIXING AND SYNCHRONIZATION	19
9 MEDIA	19
9.1 AUDIO	20
9.2 VIDEO	20

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

10 CODEC SPECS21

10.1 TIP HD VIDEO ENCODER REQUIREMENTS21

10.2 TIP CIF VIDEO ENCODER REQUIREMENTS22

10.3 TIP PRESENTATION VIDEO ENCODER REQUIREMENTS (1 & 5 FPS)22

10.4 TIP PRESENTATION VIDEO ENCODER (30FPS) REQUIREMENTS22

10.5 TIP AUDIO ENCODER REQUIREMENTS23

10.6 TIP AUDIO ACTIVITY METRIC CALCULATION23

11 CHANGES FROM 1.6 PROFILE.....24

12 REFERENCES.....25

1. Introduction

The Telepresence Interoperability Protocol (TIP) is a signaling protocol used by high end video conferencing devices to signal and negotiate capabilities complimentary to those which are signaled and negotiated in SIP/SDP [1] [3]. TIP signaling utilizes the Real-time Transport Protocol (RTP) and RTP Control Protocol (RTCP)."

Though TIP as a protocol does not restrict device capabilities or media configurations, these set of accompanying documents define the different Cisco TIP implementation profiles, which indicate device capabilities or media configurations needed to achieve interoperability with Cisco TelePresence devices. These documents will be updated from time to time as Cisco TelePresence capabilities evolve, indicated by a new revision number that generally track Cisco software releases.

TIP systems built to be integrated in to a Cisco TelePresence system deployment will need to operate seamlessly with the Cisco Unified Communications Manager (CUCM) architecture and products, appearing as CUCM SIP devices with audio and video capabilities. CUCM allows SIP endpoints to connect as generic, standard endpoints per the publically available document(s) listed [10] in the References section. No licenses for proprietary SIP extensions are required.

A TIP device is capable of handling multiple audio and video streams. The devices negotiate the number of media streams they will exchange, and media sources are switched when necessary to always present the viewer with the active session participants.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

This document specifies the Cisco 1.6b TIP profile for a single screen TIP-compliant endpoint. The profile includes requirements related to SIP signaling, TIP signaling, media encoding, and general behavior. The document takes into consideration scenarios in which a TIP-compliant single screen endpoint is communicating with another TIP-compliant single screen endpoint, triple screen endpoint, or multi-point server.

2 Single screen endpoint general capabilities

This section provides general requirements for a single screen telepresence endpoint. More details will be covered in later sections. The general requirements include:

1. SIP signaling
2. H264 video encoding and decoding at 1080P and/or 720P as well as XGA and CIF resolutions
3. AAC-LD audio encoding and decoding
4. G711 audio encoding and decoding
5. G722 encoding and decoding support is optional
6. One input video device that can be encoded using H264 codec at either 720P or 1080P resolution as well as CIF resolution simultaneously
7. An auxiliary video device (aka. presentation) that can be encoded using H264 codec at an XGA resolution
8. One input audio device that can be encoded using AAC-LD codec
9. An auxiliary audio device (aka. presentation) that can be encoded using AAC-LD codec
10. Ability to mix all audio inputs and encode them using G711 codec at the same time as encoding the individual inputs using AAC-LD. G722 can be optionally used to encode the mix if G722 is supported by the endpoint
11. Ability to receive and decode one H264 encoded stream at 1080P, 720P, or CIF resolutions as well as an H264 encoded stream at XGA resolution
12. Ability to receive and decode four AAC-LD audio streams or three AAC-LD streams and one G711/G722 stream
13. Ability to mix up to four of the received and decoded AAC-LD and G711/G722 audio streams
14. RTP/RTCP support using AVP profile

3 SIP signaling

1. A TIP-compliant endpoint is a UC SIP line device that MUST implement the UC SIP line specifications [10].

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

2. A TIP-compliant endpoint **MUST** offer and negotiate a single audio media line and a single video media line in SDP [2] [3].
3. A TIP-compliant endpoint **MUST** be able to transmit DTMF tones using KPML [13] or 2833 [12]
4. A TIP-compliant endpoint **SHOULD NOT** transmit SIP INFO [14] for codec control when TIP has been successfully negotiated.
5. Standard SIP features such as hold/resume **MUST** be supported as specified in the UC SIP line specification [10].
6. A TIP-compliant endpoint **SHOULD NOT** during hold or depend on receiving RTCP packets.
7. A TIP-compliant endpoint **MUST** send and receive mid-call INVITEs that specify updated video bit rates following a successful TIP negotiation. More detailed requirements on this behavior are included later in this document.

3.1 SDP Audio Signaling

1. A TIP-compliant endpoint **MUST** specify AAC-LD as the first codec in the SDP audio media line. In other words only an AAC-LD codec can be negotiated in SIP for devices supporting TIP.
2. It is **STRONGLY RECOMMENDED** that a TIP-compliant endpoint uses 96 as its default AAC-LD dynamic payload type. If another payload type is used, a TIP-compliant endpoint **MUST** support asymmetric payload types and **MUST** support dynamic changes in payload types while media is active.
3. A TIP-compliant endpoint **MUST** use RFC 3640 [15] and the aac-hbr mode in its AAC-LD SDP signaling.
4. The AAC-LD requirements specified in 10 **MUST** be supported even when contradictory to what is received in the audio SDP ftmp line.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .


```
m=audio 16384 RTP/AVP 96 0 99 101
b=TIAS:64000
a=rtpmap:96 mpeg4-generic/48000
a=fmtp:96 profile-level-
id=16;streamtype=5;mode=AAC-
hbr;config=11B0;sizeLength=13;indexLength
=3;indexDeltaLength=3;constantDuration=4
80
a=rtpmap:0 PCMU/8000
a=rtpmap:99 L16/48000
a=rtpmap:101 telephone-event/8000
a=fmtp:101 0-15
```

Figure 1: Sample audio SDP for first TIP endpoint offer

3.2 SDP video signaling

1. A TIP-compliant endpoint **MUST** signal H264 codec in its video media line [7].
2. A TIP-endpoint **MUST** support the reception of a profile-level-id value of “420028” as well as a placeholder value of “ABCDEF”.
3. It is **RECOMMENDED** that a TIP-compliant endpoint indicates a profile-level-id value of 420028 and packetization-mode =1 in its SDP signaling.
4. It is **STRONGLY RECOMMENDED** that a TIP-compliant endpoint uses 112 as its default dynamic H264 payload type. If another payload type is used then the endpoint **MUST** support asymmetric payload types and **MUST** support dynamic changes in payload types while media is active.
5. A TIP-compliant endpoint **MUST** include a b=TIAS [16] field associated with the video media line in every SDP offer and answer. For the initial call setup and after resume (i.e., first reINVITE transaction resuming the media), the value of the b=TIAS field **MUST** be that of a single HD video stream.
6. The b=TIAS value for the initial call setup and after the resume **MUST** be equal to or larger than .936 Mbps. The negotiated bit rate value is calculated as the minimum of the b=TIAS values in the SDP offer and answer. The negotiated bit rate value determines the maximum video resolution for the call. A negotiated value above 2.25 Mbps will result in 1080P resolution. A negotiated value between .936 and 2.25 will result in a 720P resolution. Values below .936 Mbps will cause the call to be dropped.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

Negotiated HD video bit rates	HD video resolution
2.25 – 4 >	1080P
.936- 2.25	720P
< .936	Call drop

Table 1: Bit rate to video resolution mapping

7. A TIP-compliant endpoint **MUST NOT** initiate any mid-call INVITE transactions after call setup or after resume transactions until TIP negotiation has completed.
8. All mid-call INVITEs, after TIP negotiation has completed and until the completion of a hold transaction, **MUST** have the b=TIAS value set to the sum of the bit rates of all HD video streams negotiated in TIP plus the presentation bit rate according to the first presentation frame rate negotiated in the current TIP session. Note that the first presentation bit rate is included irrespective of whether the presentation is active or not and irrespective of whether another presentation frame rate/bit rate has been negotiated. Below is the mapping between presentation frame rates and presentation bit rates.

Presentation frame rate	Presentation bit rate
30	4 Mbps
5	0.5 Mbps
1	100 Kbps

Table 2: Frame rates to bit rates mappings

9. A TIP-compliant endpoint **MUST** send a mid-call INVITE once TIP negotiation is completed, if it has initiated the call and the remote peer has not specified itself as a multi-point server in the TIP negotiation.
10. The negotiated bit rate **MAY** be changed mid-call by sending a mid-call INVITE with a new b=TIAS value.
11. A TIP-compliant endpoint **MUST** recalculate the negotiated bit rate for a single video stream for each mid-call INVITE transaction and adjust its video encoder accordingly.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

```
m=video 16386 RTP/AVP 112  
b=TIAS:2250000  
a=rtpmap:112 H264/90000  
a=fmtp:112 profile-level-  
id=ABCDEF;packetization-  
mode=1
```

Figure 2: Sample TIP-compliant video SDP

For Evaluation Only

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

4 Sample SIP call flows

4.1 Endpoint calling another endpoint




Figure 3: TIP endpoint calling another endpoint

Figure 3 shows a TIP endpoint dialing another TIP endpoint. The first INVITE transaction negotiates a single audio and video media line with H264 and AAC. The video resolution is determined by the bit rates specified by the b=TIAS parameter. As stated in 3 the video bit rate in this offer/answer exchange represents a single HD video stream.

Once each device has the media information of the other side, at the end of the first SDP offer/answer exchange, TIP negotiation MUST start on both the audio and the video channels. Once TIP has completed on the audio channel (see 5 for definition of TIP negotiation completion), endpoints can start audio transmission of all audio segments negotiated in TIP.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

Once TIP has completed on the video channel, endpoints can start video transmission on all video segments negotiated in TIP. Moreover once TIP has completed on the video channel, the calling endpoint MUST send a mid-call INVITE which updates the video bit rate according to the number of video streams and the presentation frame rate negotiated in TIP (see 3 for more details on bit rate negotiation). Note that the mid-call bit rate negotiation could end up downgrading the video resolution or bit rate from that negotiated in the initial call setup, due to policies enforced by UCM.

4.2 TIP endpoint calling a TIP multi-point server




Figure 4: TIP endpoint calling a TIP multi-point server

Figure 4 shows a TIP endpoint calling a TIP multi-point server to join an ongoing multi-point session. This call flow is similar to that of two endpoints calling each other except that it is the multi-point server that ALWAYS initiates the mid-call INVITE to update the media bit rates, once the TIP negotiation has completed on the video channel.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

4.3 TIP endpoint calling a TIP multi-point server as the first participant

Figure 5 shows a TIP endpoint dialing into a TIP multi-point server as the first participant. This flow is similar to the previous flow except that once TIP finishes, the multi-point server will send a mid-call INVITE putting the call on hold and stopping media transmission. The call will be resumed once a second participant joins the multi-point session. One thing to note is that the SDP hold message will carry the video bit rate in the b=TIAS parameter, representing the value negotiated in TIP. The endpoint SDP answer will do the same.

4.4 Resuming a TIP call after hold

This call flow is identical to Figure 4. At resume time the TIP negotiation **MUST BE** repeated and the same strategy for bit rate negotiation is repeated. No decisions are made at resume time based on what was negotiated before the hold. A call is identified as on hold if the SDP at the audio media line level has connection information (c=) specifying a 0.0.0.0 IP address or has a send-only or inactive attribute. The same information specified at the session level while omitted at the audio media line level will also indicate hold.

A call is resumed when a non-hold SDP is received following a hold SDP.

4.5 Reducing the bit rate in a call

In this example, a TIP endpoint has joined a multi-point conference and the negotiated bit rate for a single video stream was 4 Mbps. At some point the TIP multi-point server needs to reduce the bit rate of the conference to 2.5 Mbps, because a new endpoint, which can only handle 2.5 Mbps per video stream, has joined the conference. The multi-point server will send a mid-call INVITE to the TIP endpoint, similar to the mid-call INVITE in Figure 4, specifying a lower bit rate than the one negotiated in the previous INVITE transaction.

Note that the new bit rate will be the desired bit rate per stream multiplied by the number of HD video streams negotiated in TIP plus the presentation bit rate. As before, the presentation bit rate will be added irrespective of whether or not the presentation is active at this time. Also, the presentation bit rate will be calculated based on the frame rate first negotiated in the TIP session irrespective of whether this frame rate has been downgraded later or not.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.




Figure 5: TIP endpoint joining a multi-point session as first participant

5 Initial TIP signaling

Single screen endpoints that are TIP-compliant MUST adhere to all of the MUST requirements specified in the TIP document [11] as well as the MUST requirements in this document.

5.1 MUXCTRL Packet

1. In a video session, the AVPF profile MUST be supported and signaled in the MUXCTRL packet as specified in the TIP specs [11]. This in turn mandates support for the transmission and reception of the RTCP video feedback packets as specified in the TIP specs [11]
2. In an audio session, the profile MUST be AVP.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

3. The options field of the MUXCTRL packet **MUST** be set to 0x00.
4. The number of transmitted streams **MUST** be set to 2 for a video session when no presentation is to be transmitted, and set to 3 when presentation transmission is requested.
5. The number of transmitted streams **MUST** be set to 3 for an audio session.
6. The number of received video streams **MUST** be set to 2.
7. The number of received audio streams **MUST** be set to 5.
8. The transmit video positions **MUST** contain only center and legacy center when no presentation transmission is requested.
9. The auxiliary transmit video position **MUST** be set when presentation transmission is requested.
10. The transmit audio positions **MUST** contain only center, legacy mix, and auxiliary.
11. The receive video positions **MUST** contain center and auxiliary.
12. The receive audio positions **MUST** contain center, left, right, legacy, and auxiliary.
13. TIP endpoints **SHOULD** set the conference identifier field, or if the identifier is not known, set the field to 0.

5.2 MediaOpts Packet

1. TIP endpoints **MUST** indicate support for transmission of Audio Activity Metric and **MUST NOT** indicate support for reception of Audio Activity Metric.
2. TIP endpoints **MUST** support the reception of Audio Dynamic Output Channel.
3. TIP endpoints **MUST NOT** indicate support for transmission of the Audio Dynamic Output Channel and **MUST** set output positions in all TIP-CSRCs to zero.
4. TIP endpoints **MAY** indicate support and use of G722 encoding for legacy audio streams.
5. TIP endpoints **MUST** indicate support for the transmission of the video Refresh flag but **MUST NOT** indicate support for the reception of the flag.
6. TIP endpoints **MUST** indicate support for Inband Parameter Sets (SPS/PPS) both for transmission and reception.
7. TIP endpoints **MAY** signal support for CABAC (Please see exception note in 11.1)
8. TIP endpoints **MAY** signal support for LTRP and GDR.
9. TIP endpoints **MUST** signal support for the maximum auxiliary frame rate that they can support. Note that frame rates are symmetric and the maximum can be 30, 5 or 1.
10. TIP endpoints are **RECOMMENDED** to support 30 fps as their maximum frame rate.
11. TIP endpoints **MUST** support 5 and 1 fps auxiliary frame rates.
12. TIP endpoints **MAY** signal a Satellite deployment Transmitter profile if it is known that this endpoint is connected using a satellite link.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

5.3 TIP Negotiation and general mid-session signaling rules

1. A TIP endpoint **MUST NOT** start media transmission until the TIP negotiation has finished. TIP negotiation is finished once the following has completed:

- a. Local MUXCTRL packet has been sent and a remote ACK was received.
- b. Remote MUXCTRL has been received and an ACK was sent.
- c. Local MediaOpts packet has been sent and an ACK was received.
- d. Remote MediaOpts packet has been received and ACK was sent.

Note that TIP can (and will) complete at one peer prior to the other. Implementation **MUST** be able to handle such scenarios.

2. The number of transmitted streams **MUST NOT** exceed the number of streams the remote peer is capable of receiving
3. Only positions indicated as supported by the remote peer can be used in the CSRC received position
4. Typically the number of transmitted streams is the minimum of what the local endpoint can transmit and what the remote peer can receive. The exception is for legacy streams, which **MUST NOT** be transmitted, except if the remote peer indicates its capability to receive the legacy streams **AND** the remote peer indicates that it is a multi-point server by signaling the isfocus parameter in its MUXCTRL packet.
5. Below is the maximum number of streams that will be sent and received when a single screen TIP endpoint communicates with a remote peer supporting one of the TIP profiles:
 - a. Remote peer is a triple screen TIP endpoint
 - i. Transmitted audio streams: 2
 - ii. Received audio streams: 4
 - iii. Transmitted video streams: 2
 - iv. Received video streams: 2
 - b. Remote peer is a single screen TIP endpoint
 - i. Transmitted audio streams: 2
 - ii. Received audio streams: 2
 - iii. Transmitted video streams: 2
 - iv. Received video streams: 2
 - c. Remote peer is a multi-point server requiring legacy stream support:
 - i. Transmitted audio streams: 3
 - ii. Received audio streams: 5
 - iii. Transmitted video streams: 3
 - iv. Received video streams: 2

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

- d. Remote peer is a multi-point server requiring no legacy stream support:
 - i. Transmitted audio streams: 2
 - ii. Received audio streams: 4
 - iii. Transmitted video streams: 2
 - iv. Received video streams: 2
6. TIP endpoints MUST NOT generate a second MediaOpts packet within the same TIP session¹ in which there have been changes to the supported presentation frame rate or any other media capabilities.
7. TIP endpoints MUST support the ability to receive MediaOpts packet that change the supported auxiliary frame rate, but only within the limit of the initially negotiated maximum auxiliary frame rate.
8. TIP endpoints MUST silently discard any received TIP packet with an unrecognized RTCP APP packet subtype.
9. TIP endpoints MUST silently discard any received TIP packet with an RTCP APP name other than "xcts".
10. TIP endpoints MUST respond to ECHO requests as specified in the TIP specs.
11. TIP endpoints MUST support the reception of the media flow control request and process it according to the TIP specs [11].
12. TIP endpoints MUST NOT generate media flow control requests.
13. TIP endpoints MUST support the reception of the video refresh request and process it according to the TIP specs.
14. TIP endpoints MUST be able to receive a video refresh request that does not include the Flags field. On receiving such a request, the endpoint can generate an IDR or a GDR. Note that GDRs can only be generated if GDR support has been negotiated for the current TIP session.
15. TIP endpoints MAY generate video refresh requests though it is NOT RECOMMENDED to use this mechanism when packet losses are encountered. Alternatively the video feedback mechanism should be used for reporting loss.

6 Presentation Signaling

Permission to present is requested and released using the video session MUXCTRL packet with the auxiliary video *transmission* position. The video session MUXCTRL packet with the auxiliary video *receiving* position is used ONLY by multi-point servers to grant permission to present.

¹ A TIP session is initiated at call setup and after a hold or resume transaction. It is identified by a unique TIP SSRC value.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

A TIP endpoint can receive a MUXCTRL packet that does not change the presentation state. The endpoint MUST process such packets with no disruption to presentation media.

6.1 Transmitting and receiving permission-to-present requests in a multi-point session

To request permission to present, a TIP endpoint MUST send a MUXCTRL packet on the video session setting the transmit video auxiliary position to 1 and incrementing the number of transmitted video streams by 1.

If the request is granted, the multi-point server will send a MUXCTRL packet on the video session setting the receive auxiliary video position to 1. Once the endpoint ACKs the request it can start transmitting its presentation video and audio.

If the multi-point server denies the request due to conflict with another endpoint that already has permission to transmit, the multi-point server will send a MUXCTRL packet setting the auxiliary *receive* video position to 0. This request will typically have the auxiliary video *transmit* position set to 1 indicating that the multi-point server has another source ready to transmit.

A TIP endpoint receiving a request for permission to present MUST grant the request, via acking it and starting its presentation receivers. If the endpoint was already transmitting presentation prior to receiving the permission-to-present request, it MUST stop its presentation transmission on both audio and video channels and ACK the request.

TIP endpoints MUST NOT deny permission-to-transmit requests. In other words TIP endpoints MUST NOT send a MUXCTRL packet that has the auxiliary receive position set to zero.

6.2 Transmitting and receiving permission-to-present requests in a point-to-point session

To request permission to present, a TIP endpoint MUST send a MUXCTRL packet on the video session, setting the transmit video auxiliary position to 1 and incrementing the number of transmitted video streams by 1.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

The request is granted once the remote endpoint ACKs the request. Once the ACK packet is received, the endpoint can start transmitting its presentation video and audio.

A presentation conflict can occur when a MUXCTRL is received from the remote peer requesting permission to present at the same time that a local permission-to-transmit has been sent. TIP resolves the conflict by specifying the endpoint that has initiated the call as the winner of the conflict. To achieve such a result the following behavior is a MUST in the case of a presentation conflict:

1. Before it considers itself the new presenter, the endpoint that has initiated the call MUST wait for a new MUXCTRL packet from the remote peer releasing its permission-to-present request (see release permission-to-present section below).
2. The endpoint that has not initiated the call MUST send a new MUXCTRL packet releasing its permission-to-present request
3. Both endpoints MUST ACK all MUXCTRL packets received

A TIP endpoint receiving a permission-to-present request MUST grant the request, via acking it and starting its presentation receivers, except in the case of a conflict, where the above stated behavior for conflict resolution MUST be followed. If the endpoint was already transmitting presentation prior to receiving the permission-to-present request, it MUST stop its presentation transmission on both audio and video channels and ACK the request.

A TIP endpoint MUST NOT deny any permission-to-transmit requests by sending a MUXCTRL that has the auxiliary receive position set to zero.

6.3 Transmitting and receiving permission-to-present release requests

To release permission to present, the endpoint MUST send a MUXCTRL packet on the video session, setting the transmit video auxiliary position to 0 and decrementing the number of transmit positions.

Note that in a multi-point session an endpoint which has previously sent a permission-to-present that was not granted MUST still release the permission-to-present when it is no longer interested in transmitting presentation.

In point-to-point scenarios when the endpoint receives permission-to-present release request, it MUST ACK the request. If the endpoint is interested in presentation transmission then it MUST send a new MUXCTRL requesting permission to present.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

6.4 Receiving a request-to-present grant in a multi-point session

A multi-point server can grant permission to present to an endpoint after it has denied the request initially. This is the case when a conflict occurs between multiple endpoints requesting to present at the same time and resulting in the multi-point server granting only one request while denying others. Once the winning endpoint releases its permission to present, the multi-point might grant the permission to present to the endpoint whose request was previously denied. In this case the endpoint will receive a MUXCTRL packet with the receive auxiliary video position set to 1 and the auxiliary transmit video position set to 0. If the endpoint is still interested in presentation transmission, it can start transmitting presentation. Otherwise the endpoint MUST send a new MUXCTRL packet requesting a permission-to-present release.

7 Presentation frame rate negotiation

7.1 Initial frame rate negotiation

As specified in the TIP specs [11], the MediaOpts packet is used for frame rate negotiation. It is RECOMMENDED that TIP endpoints support and signal a 30 fps capability in the MediaOpts packet. Once a TIP endpoint has signaled its initial presentation frame rate capability, it MUST NOT change it during the same TIP session. The negotiated initial frame rate is calculated as the minimum of what was signaled by both peers. Note that the initial frame rate is what will be used to determine the presentation bit rate included in the SDP video b=TIAS [16] line irrespective of whether or not the frame rate has changed later within the TIP session.

It is important to note that when an endpoint signals a frame rate capability, such as 30 fps, this endpoint MUST also support all lower frame rates such as 5 and 1 fps. However, an endpoint with a negotiated frame rate such as 30 fps MUST NOT transmit presentation using a different frame rate such as 5 fps without first receiving a MediaOpts packet negotiating the new frame rate.

7.2 Signaling a new frame rate

TIP endpoints MUST NOT dynamically change their signaled frame rate. However TIP endpoints MUST support receiving mid-session MediaOpts packets that can lower or increase the negotiated frame rate. Note that the negotiated frame rate MUST NOT be higher than the initially negotiated frame rate in the TIP session. Once the endpoint ACKs the MediaOpts packet, any new presentation transmitted MUST use the new frame rate.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

8 Audio mixing and synchronization

In a multi-point session or when communicating with a triple screen TIP endpoint, a single screen TIP endpoint will receive multiple audio streams. These audio streams will each have a different receiver position in the CSRC. The single screen endpoint must mix and play out these different audio streams.

Note that some, or all, of the audio streams to be mixed could be coming from the same remote endpoint. Such audio streams can be identified as they share the same TIP-CSRC sampling clock ID. A TIP endpoint SHOULD use the audio SRs to synchronize audio between streams that share the same CSRC sampling clock ID.

9 Media

1. TIP endpoints MUST handle dynamic switches of SSRCs [4] and their associated CSRCs on received video and audio streams. The CSRC receive position identifies that this new SSRC is to replace the previous SSRC that was associated with the CSRC with the same receive position.
2. All audio and video SSRCs MUST NOT have only zeros in their last 8 bits.
3. TIP endpoints MUST change their audio and video streams' SSRCs and CSRCs after a hold/resume transaction.
4. Video SSRCs and CSRCs values MUST change when switching presentation streams from 30 fps to 1 or 5 fps and vice versa.
5. TIP endpoints MUST support remote RTP senders and receivers corresponding to the same position yet using different SSRCs. For example a TIP endpoint might receive an RTCP RR or an RTCP feedback packet from a center position receiver with a source SSRC different from the source SSRC of the center position's RTP packets.
6. TIP endpoints MUST support the flow control TIP packet, both for transmitting and receiving video streams. The receive flow control will be used by a multi-point server to inform the endpoint that no media will be transmitted by the server using the receive position specified in the flow control packet target CSRC. The transmit flow control will be used by the multi-point server to inform the endpoint that no media should be transmitted using the transmit position specified in the flow control packet target CSRC.
7. TIP Endpoints MUST always transmit media using all source positions negotiated in TIP, unless a transmit flow control packet to turn off that specific position was received.
8. TIP endpoints MUST transmit RTCP Sender Reports [4].
9. TIP endpoints MUST silently discard any non-RTP packets, such as DTLS or STUN Keepalive packets received on the video and audio RTP sessions.
10. TIP endpoints MUST silently discard any RTP packets with an unknown payload type.

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

9.1 Audio

1. All non-legacy audio streams **MUST** be transmitted using AAC-LD (see 10 for codec requirements) and using RFC 3640 with AAC-hbr mode [15]
2. TIP endpoints **MUST** transmit 2 AAC audio frames (10 msec per frame) msec in AAC audio packets
3. TIP endpoints **MUST** send audio activity metric byte for all AAC audio streams as specified in the TIP specs [11] when the Audio Activity Metric support is negotiated in TIP
4. TIP endpoints **MUST** set the Audio Activity Metric associated with presentation audio to a value of 99
5. TIP endpoints **MUST NOT** send the audio activity metric byte for G711 or G722 legacy streams
6. TIP endpoints **MUST** be able to deal with periods where no audio packets are received on one or more of its active audio positions without disrupting the call. The recommendation is to use video streams to detect network problems and act on them. Video streams will receive a receive flow control off packet when no video packets are available for transmission on a specific position.
7. TIP endpoints **MUST** be able to deal with receiving the same audio stream with discontinuous sequence numbers. Note that for video sequence numbers will only be discontinuous during an SSRC switch whereas in the case of audio this might not always be true
8. TIP endpoints **MUST** support mixing of audio streams that are sent using the same output position and different receive positions
9. TIP endpoints **SHOULD** use received audio Sender Reports to synchronize audio between different SSRCs that share the same CSRC sampling clock ID.
10. TIP endpoints **MUST** generate accurate and frequent audio RTCP Sender Reports for audio sources to allow remote peers to perform cross-media synchronization
11. When dynamic output channels are not negotiated, TIP endpoints **MUST** include zero in the 4 TIP-CSRC bits corresponding to output positions

9.2 Video

1. TIP endpoints **MUST** include zero in the 4 video TIP-CSRC bits, corresponding to the dynamic output positions.
2. All HD and auxiliary H264 video streams **MUST** be packetized using packetization mode "1" [7]. The following NAL types are supported:
 - 1 (non-IDR)
 - 5 (IDR)
 - 6 (SEI, only subtype 6 [recovery point] is supported for GDRs)
 - 7 (SPS)
 - 8 (PPS)

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

3. All CIF H264 video streams MUST be packetized using packetization mode 0 [7].
4. All video streams except for auxiliary MUST be transmitted using a 30 fps or 29.97 fps.
5. Auxiliary streams MUST be transmitted using the frame rate signaled in the TIP session.
6. TIP endpoints' video frames sampling instances ,and their corresponding RTP timestamps, MUST always correspond to regular intervals that is based on the video clock rate and the video frame rate. For example a 30 fps TIP video stream using a 90KHz clock can only generate video frames every 3000 clock ticks. A 5 fps TIP video stream using a 90 KHz clock can only generate video frames every 18000 clock ticks.
7. TIP endpoints MUST send the video refresh flag for all video streams when support for video refresh flag is negotiated in TIP.
8. TIP endpoints MUST support in-band transmission of the SPS and PPS as the first two NALs in each I-frame. TIP endpoints MUST support in-band transmission of the SPS, PPS, and SEI recovery point NAL as the first three NALS in each GDR.
9. TIP endpoints MUST support transmission and reception of RTCP video feedback as specified in the TIP SPECS. [11]
10. TIP endpoints MUST transmit a repair frame as soon as a negative video feedback report is processed.

10 Codec Specs

10.1 TIP HD Video Encoder Requirements

1. MUST generate H264 Main Profile compatible bit stream
2. MUST support CAVLC
3. MUST support CABAC as a negotiated option
4. MUST support 1280x720 or 1920x1072 resolution
5. MUST support fixed frame rate: 30 fps or 29.97 fps
6. MUST generate one macro block-row per slice
 - 1280x720: 45 slices per frame, each slice must be 80 macro blocks in length
 - 1920x1072: 67 slices per frame, each slice must be 120 macro blocks in length
7. MUST support `deblocking_filter_control_present = 1` & `disable_deblocking_filter_idc = 1`
8. MUST only use interprediction blocks of size 16x16
9. MUST only use one reference picture
10. Each NAL MUST be less than 3320 bytes in size
11. POC MUST increment by 2 every frame
12. **MUST NOT USE SPS IDs in the range of 10 to 20**
13. Long term reference pictures (LTRPs) MAY be used for error concealment. LTRPs require a four frame picture buffer. LTRPs use H.264 standard picture buffer management. LTRPs are optional and can be disabled.
14. Gradual decoder refresh pictures (GDRs) MAY be used at the start of a sequence instead

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .

of an instantaneous decoder refresh picture (IDR). A recovery point SEI precedes the GDR. The SEI always has the broken_link_flag set to 0. GDRs are optional and can be disabled.

10.2 TIP CIF Video Encoder Requirements

1. MUST support H264 Baseline Profile compatible bit stream
2. MUST support 352x288 resolution
3. May support variable frame rate up to 30 fps
4. Uses one reference picture from previous frame
5. Each NAL MUST be less than 3320 bytes in size

10.3 TIP Presentation Video Encoder Requirements (1 & 5 fps)

1. MUST support H264 Baseline Profile
2. MUST support 1024x768 resolution
3. MUST support Fixed frame rate: 1 or 5 fps
4. MUST support the use of one reference picture from previous frame
5. MUST support one macro block-row per slice,
-1024x768: 48 slices per frame, each slice must be 64 macro blocks in length
6. MUST support deblocking_filter_control_present = 1 & disable_deblocking_filter_idc = 1
7. MUST only support inter-prediction blocks of size 16x16
8. Each NAL MUST be less than 3320 bytes in size
9. POC MUST increment by 2 every frame

10.4 TIP Presentation Video Encoder (30fps) Requirements

1. MUST support H264 Main Profile compatible bit stream
2. MUST support CAVLC
3. MAY support CABAC as a negotiated option
4. MUST support 1024x768 resolution
5. MUST support fixed frame rate: 30 fps or 29.97 fps
6. MUST support one macro block-row per slice
7. -1024x768: 48 slices per frame, each slice must be 64 macro blocks in length
8. MUST support deblocking_filter_control_present = 1 & disable_deblocking_filter_idc = 1
9. MUST only support inter-prediction blocks of size 16x16
10. MUST support one reference picture
11. Each NAL MUST be less than 3320 bytes in size

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

12. POC MUST increment by 2 every frame
13. **MUST NOT USE SPS IDs in the range of 10 to 20**
14. Long term reference pictures (LTRPs) MAY be used for error concealment. LTRPs require a four frame picture buffer. LTRPs use H264 standard picture buffer management. LTRPs are optional and can be disabled.
15. Gradual decoder refresh pictures (GDRs) MAY be used at the start of a sequence instead of an instantaneous decoder refresh picture (IDR). A recovery point SEI precedes the GDR. The SEI always has the broken_link_flag set to 0. GDRs are optional and can be disabled.

10.5 TIP Audio Encoder Requirements

Codec: G.711 (u-law)
Frame Size: 80 samples
CNG is OFF
Packetization interval: 20ms

Codec: G.722
Frame Size: 160 samples
Sampling Rate: 16KHz
Bit Rate: 64 kbps
CNG is OFF
Packetization interval: 20ms

Codec: AACLD
Frame Size: 480 samples
Sampling Rate: 48KHz
Bit Rate: 64 kbps
Mono channel
Transmux = 0
PNS (Perceptual Noise Substitution): enabled
LTP (Long Term Prediction): disabled
Packetization interval: 20ms

10.6 TIP Audio Activity Metric Calculation

The audio activity metric is an integer value from 0-99 computed by comparing the current audio power level to a measured noise floor. If the current power is less than or equal to the floor then the metric value should be 0. If the current power is between 1dB and 20dB above the floor then the metric value should be between 1 and 89. If the current power is between

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

20dB and 40dB above the floor then the metric value should be between 90 and 98. If the current power is greater than 40dB above the floor then the metric value should be 99.

The calculation of the noise floor should be dynamic during the course of the call, although historical information may be used as the initial value. The goal of the noise floor is to eliminate artificially high audio activity metric values due to constant background noise.

11 Changes from 1.6 profile

1. CABAC is now optional for HD and 30 fps auxiliary encoders. MediaOpts packet signaling has changed to reflect this update. However, CABAC is used by default and can only be turned off for multi-point sessions in deployments using the Cisco TelePresence 1.6.4 software release or later for the CTMS multipoint server, and CTS 1.6.5 or later for the endpoints.
2. Added restrictions on the SPS IDs which were erroneously omitted from the 1.6 profile.
3. Added clarification for what constitutes a hold/resume scenario that triggers a TIP re-negotiation
4. Mandated SSRC and CSRC changes for a resumed call
5. Added support for RTP senders and receivers of the same endpoint using different SSRCS
6. Corrected the fact that not all audio streams transmitted by TIP endpoints are AAC-LD
7. Clarified that the video activity metric byte is not to be transmitted for G711/G722 streams
8. Added RTP video timestamps requirement
9. Indicated the possibility of receiving a video refresh request without a FLAG field and how an endpoint should deal with such request

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip.

12 References

- [1] IETF RFC 3261 "SIP: Session Initiation Protocol"
- [2] IETF RFC 3264 "An Offer/Answer Model with the Session Description Protocol (SDP)"
- [3] RFC 2327 "SDP: Session Description Protocol"
- [4] IETF RFC 3550 "RTP: A Transport Protocol for Real-Time Applications"
- [5] IETF RFC 3551 "RTP Profile for Audio and Video Conferences with Minimal Control"
- [6] IETF RFC 4961 "Symmetric RTP/RTP Control Protocol (RTCP)"
- [7] IETF RFC 3984 "RTP Payload Format for H.264 Video"
- [8] IETF RFC 4585 "Extended RTP Profile for Real-time Transport Control Protocol (RTCP)-Based Feedback (RTP/AVPF)"
- [9] IETF DRAFT draft-ietf-avt-rtp-and-rtcp-mux-07 "Multiplexing RTP Data and Control Packets on a Single Port"
- [10] "Cisco Unified Communications Manager SIP Line Messaging Guide (Standard)"
http://www.cisco.com/en/US/docs/voice_ip_comm/cucm/sip_msg/line_std/8_0_1/siplst801.pdf
- [11] Telepresence Interoperability Protocol 6.0
- [12] IETF RFC 2833 "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals"
- [13] IETF RFC 4730 "A Session Initiation Protocol (SIP) Event Package for Key Press Stimulus (KPML)"
- [14] IETF RFC 5168 "XML Schema for Media Control"
- [15] IETF RFC 3640 "RTP Payload Format for Transport of MPEG-4 Elementary Streams"
- [16] IETF RFC 3890 "A Transport Independent Bandwidth Modifier for the Session Description Protocol (SDP)"

END OF DOCUMENT

Your rights to use, copy, modify or distribute this document are governed by the TIP Evaluation Agreement. Information about that Agreement is available at www.imtc.org/tip .